



# DHC Hydraulic Presses

## Benchtop and Automation Solutions

### Standard Cast Iron Frame Configurations

With Shank Tool Holder	DHC-3	DHC-5
Tonnage	3.3	5.5
Stroke (Inches)	5.9"	5.9"
Open Height (Inches)	9.8"	9.8"
Approach Speed (IPM)	368	315
Pressing Speed (IPM)	153	97
Retract Speed (IPM)	263	140
Bed Table (W" x D")	17.7"x14.2"	17.7"x14.2"
Power	230V/3PH	230V/3PH
Hydraulic Motor (HP)	2	2
Weight (lbs.)	775	795
Shank Hole Diameter (In.)	1.18"	1.18"
Throat Distance (In.)	6.3"	6.3"

- Standard pressure control
- Standard speed control
- Allen Bradley PLC Control Package with Operator Interface
- 1 year warranty on material and workmanship
- Compact heavy duty design built for reliability
- Available in stock or by special order
- Energy efficient system
- Low noise output for quiet operation

DHC: Economical cast frame press with standard configurations only

### Available Options

Shut Height	Multiple Control Platforms
Complete Integration Solutions	460V/3PH Power System
Complete Automation Solutions	Pressure Switch
Light Curtain Guarding	Air/Water Cooler
Bolt on Expanded Metal Guarding	Reservoir Heater
Machining Requirements	Heated Platens
Work Table with Casters	Increased Tonnage (+40 Tons)

\*Other options available upon customer request.



\*Some options shown

