



DHS Hydraulic Presses

Benchtop and Automation Solutions

Standard Steel Frame Configurations

With Shank Tool Holder	DHS-3	DHS-5	DHS-10	DHS-15	DHS-20
Tonnage	3.3	5.5	11	16.5	22
Stroke (Inches)	5.9"	5.9"	5.9"	5.9"	5.9"
Open Height (Inches)	11.8"	11.8"	13.8"	13.8"	13.8"
Approach Speed (IPM)	420	368	215	516	470
Pressing Speed (IPM)	175	113	88	48	46
Retract Speed (IPM)	300	163	146	263	273
Bed Table (W" x D")	19.7"x14.2"	19.7"x14.2"	23.6"x14.2"	23.6"x15.7"	27.6"x15.7"
Power	230V/3PH	230V/3PH	230V/3PH	230V/3PH	230V/3PH
Hydraulic Motor (HP)	2	3	3	3	5
Weight (lbs.)	1,145	1,367	2,205	2,755	3,300
Shank Hole Diameter (In.)	1.18"	1.18"	1.18"	1.18"	1.18"
Throat Distance (In.)	7.1"	7.1"	7.1"	8.1"	8.7"

- Standard pressure control
- Standard speed control
- Allen Bradley PLC Control System with Operator Interface
- 1 year warranty on material and workmanship
- Compact heavy duty design built for reliability
- Available in stock or by special order
- Energy efficient system
- Low noise output for quiet operation

DHS: Available with standard configurations that can be customized to your specifications

Available Options

Stroke	Multiple Control Platforms
Shut Height	460V/3PH Power System
Complete Integration Solutions	Pressure Switch
Complete Automation Solutions	Air/Water Cooler
Light Curtain Guarding	Reservoir Heater
Bolt on Expanded Metal Guarding	Heated Platens
Machining Requirements	Increased Tonnage (+40 Tons)
Guided Ram Bolster	*Other options available upon customer request.
Work Table with Casters	



*Some options shown

