



DBP Hydro-Pneumatic Presses

Benchtop and Automation Solutions

Standard Steel Frame Configurations

Air/Oil Press	DBP-3	DBP-6	DBP-10
Tonnage	3	6	10
Stroke - Working (Inches)	1"	1"	0.8"
Stroke - Total (Inches)	4"	4"	4"
Open Height (Inches)	10"	10"	12"
Boosting Ratio	1:25	1:25	1:25
Air Pressure (PSI)	43-100	43-100	43-100
Table (W" x D")	10.5"x7"	10.5"x7"	14"x9.5"
Air Consumption (Ft ³ /cyc)	1.0	2.0	2.5
Overall (W" x D")	17"x20"	15"x24"	17"x28"
Overall Height (Inches)	35"	41"	47"
Weight (lbs.)	440	550	880
Shank Hole Diameter (In.)	0.79"	0.79"	0.98"
Base Price	Call for Latest Pricing		

- Standard pressure control
- Standard speed control
- Technical online and phone support available on all models
- 1 year warranty on material and workmanship
- Compact heavy duty design built for reliability
- Available in stock or by special order
- Energy efficient system
- Low noise output for quiet operation

DBP: Air/Oil Press utilizing shop air + 120V 1 phase as standard

Available Options

Complete Integration Solutions	Multiple Control Platforms
Complete Automation Solutions	460V/3PH Power System
Light Curtain Guarding	Pressure Switch
Bolt on Expanded Metal Guarding	Air/Water Cooler
Machining Requirements	Reservoir Heater
Work Table with Casters	Heated Platens

*Other options available upon customer request.

